

REACTOR® 3

Smart Drum-to-Gun Spray Technology Expands Your Business and Improves Profitability





THERE IS NOTHING LIKE A GRACO ELECTRIC PROPORTIONER

Experienced contractors know the difference. Graco professional electric proportioners are solid investments that perform reliably, year after year.

TRUST YOUR BUSINESS AND REPUTATION TO GRACO

Graco is committed to providing the highest quality, backed by the industry's best warranty.

AMERICAN BUILT QUALITY SINCE 1926

100% factory-tested and field-proven, manufactured, assembled and supported in the USA.

INDUSTRY-LEADING WARRANTY

The industry's strongest warranty. You may never use Graco's warranty - but if you do, we will be there.



GRACO-ONLY SOLUTIONS THAT KEEP YOU SPRAYING



THE ONLY FULLY-CONNECTED DRUM TO GUN SYSTEM

- Maximize your benefits and protection with application intelligence
- Help provide professional results for first time sprayers
- Stay on ratio and improve yield with system intelligence



MAXIMIZE PRODUCTIVITY WITH REMOTE CONTROL AND MONITORING

- Remotely control your machine with the Reactor Connect app
- Easy monitoring and troubleshooting with real-time fleet dashboards
- Streamline your business with job reports and data analytics



QUICK CHANGEOVERS TO FINISH JOBS FASTER

- Quickly switch your pump between drums
- Easily move your pump in low ceiling height rigs
- Makes pump rebuilds fast and easy



EXCLUSIVE ELECTRIC TRANSFER PUMP TECHNOLOGY

- Communicates with the Reactor for improved ratio assurance and yield
- Automatically shuts down when you run out of material
- Monitors inlet pressures and selfadjusts to optimize material feed
- Quiet operation

Xcelerator

STRONGER, FASTER TO HEAT, LIGHTER HEATED HOSE DESIGN

- Improved pressure balancing and yield with independent A and B temperature control
- Longer life and improved reliability with new robust hose construction
- Internally or externally heated options to meet all your needs



FROM START TO FINISH, THE WORLD'S MOST ADVANCED SPRAY FOAM AND POLYUREA SYSTEM

The NEW fully-connected Graco Reactor 3 system is your partner in the field. With connectivity from drum to gun, you can precisely control heat, pressure and material flow for spray applications.



REACTOR 3 ELECTRIC PROPORTIONER

The ONLY Fully-Connected System From Drum to Gun

Upgrade your rig with a powerful NEW Reactor 3 proportioner, built with advanced capabilities for spray foam and polyurea applications. Reactor 3 is designed to communicate with the entire system to simplify the operator's job, optimize spray parameters and maximize productivity.

NEW ISO LUBE PUMP

- Active ISO Lube system with peristaltic pump
- Automatic timed circulation improves TSL Life
- Reduced maintenance (No check valves)
- New larger easy-to-change ISO lube bottle

NEW FLUID MANIFOLD

• Redesigned with side-mounted fluid valves for easier turning and improved control

NEW INLET FILTERS

- New easy-to-maintain design
- 2X larger filter area
- Separate temperature and pressure sensors for more accurate temperature readings

an Elite model.



REACTOR CONNECT

- Real-time dashboard and reports via cellular connectivity
- Improved cellular antenna
- New GPS antenna
- GPS location available in Reactor Connect

NEW TOUCHSCREEN ADVANCED DISPLAY MODULE (ADM)

- Large new touchscreen interface
- Intuitive operation and navigation
- All spray operations from one screen

NEW INDEPENDENT HOSE CONTROL

- · Control A and B materials to different temperatures for improved pressure balancing
- Optimizes vield

NEW ADVANCED ELECTRIC DESIGN


- Brushless motor for improved pressure/flow performance
- New temperature control boards for independent hose heat
- Voltage jumpers for easy changing between voltages
- Robust UL listed electrical hose connectors are color coded and keyed for error proof assembly
- New Reactor 3 exclusive: connect with Tier 4 engines for ADM engine diagnostic

OVAL GEAR FLOW METERS (under shroud)

- Verifies fluid ratio
- Provides real-time ratio data: displayed on the ADM and Reactor Connect
- · Accurate for a wide range of fluid viscosities

REDUCED SIZE

- Reduced footprint provides additional room in your rig
- Compact design protects the flow meters and hose connections from being damaged in your rig



NEW ADVANCED SOFTWARE FEATURES

- Katalyst: Reactor Intelligence from drum-to-gun. System communication and control that improves performance, ratio and yield.
- Auto Pressure Balance: Reactor automatically adjusts temperatures to optimize fluid pressures and maximize yield
- Supply Pump Shutdown: Automatically shuts down when you run out of material. Prevents air from entering the system that can cause off-ratio issues. (Requires Core E1 pumps)
- Smart Supply: Automatically monitors and adjusts fluid inlet pressures to compensate for high viscosity (e.g., cold) materials to keep you spraying on ratio (Requires Elite Reactor paired with Core E1 pumps)
- Resistance Control Mode: Accurately monitors and controls hose temperatures without the hassles of fluid sensors and RTD cables
- Power Management: Select desired heater wattage for reduced power consumption
- Cellular Software Updates: Automatically stay up to date with the latest Reactor software (Requires Reactor Connect)
- Jog Countdown Timer: Input a cycle count value and have the machine run and shut off after that exact value to assist if precisely flushing the system
- * Some features and software are only available on Pro and/or Elite models.

WHICH SYSTEM IS RIGHT FOR YOU?

Easy to Upgrade. Add Elite Features Later as Your Business Grows.

Purchase the Reactor 3 system that makes sense for your business now and add features along the way. The Reactor 3 line allows you to start with a Standard or Pro and upgrade to Elite capabilities at any time.

CHOOSE THE REACTOR 3 MODEL THAT BEST FITS YOU



Touch Screen ADM
Brushless Motor
Active ISO Lube Pump
Data Download (with USB)
Small Recirculation Valves
Simple Y-strainers

Software:

- Independent A & B Hose Heat
- Resistance Control Mode







All the features of Standard **PLUS**...

Larger Heater Options
Large Easy-Access Inlet Filters
Reactor Connect Cell Module
Large Recirculation Valves
Drum-Level Dipsticks

Software:

- Auto Pressure Balance
- Power Management
- Automatic Cellular Software Updates

All the features of Pro PLUS...

Katalyst Full System Control
Ratio Assurance
Inlet Temperature & Pressure Sensors
Generator Dashboard
Optimized for Core E1 Transfer Pumps

Software:

- Smart Control
- Smart Supply

SELECT YOUR PERFORMANCE LEVEL

Every Business Need is Different

Reactor 3 has a performance point to meet every business need. Whether you are just starting your business and want a reliable machine at a reasonable price or are an established business looking to expand your capabilities and improve your productivity, we have a machine that will meet your needs.

CHOOSE AN OPTION THAT MEETS YOUR NEEDS

SPRAY FOAM OPTIONS

MODEL
MOTOR
MAX FLOW
MAX PRESSURE
PRIMARY HEAT
MAX HOSE LENGTH
·

PROPORTIONER

STANDARD		PKU			ELITE		
E-20	E-30	E-20		E-	30	E-20	E-30
1.8 HP Brushless	2.5 HP Brushless	1.8 HP Brushless			HP hless	1.8 HP Brushless	2.5 HP Brushless
2 GPM	3 GPM	2 GPM		3 G	iPM	2 GPM	3 GPM
2000 psi	2000 psi	2000 psi		200	0 psi	2000 psi	2000 psi
7 kW Sngl. Block	10 kW Sngl. Block	7 kW Sngl. Block	10 kW Sngl. Block	10 kW Sngl. Block	15 kW Dual Block	10 kW Sngl. Block	15 kW Dual Block
220 ft	320 ft	220 ft		32	0 ft	220 ft	320 ft


ONS	
OPTI	
IREA	
)[YI	

PROPORTIONER	STANDARD		PRO		ELITE	
MODEL	E-XP1	E-XP2	E-XP1	E-XP2	E-XP1	E-XP2
MOTOR	1.8 HP Brushless	2.5 HP Brushless	1.8 HP Brushless	2.5 HP Brushless	1.8 HP Brushless	2.5 HP Brushless
MAX FLOW	1.5 GPM	2 GPM	1.5 GPM	2 GPM	1.5 GPM	2 GPM
MAX PRESSURE	3000 psi	3500 psi	3000 psi	3500 psi	3000 psi	3500 psi
PRIMARY HEAT	10 kW Sngl. Block	15 kW Dual Block	10 kW Sngl. Block	15 kW Dual Block	10 kW Sngl. Block	15 kW Dual Block
MAX HOSE LENGTH	220 ft	320 ft	220 ft	320 ft	220 ft	320 ft


WHAT'S INCLUDED IN EACH PACKAGE:

PACKAGE OPTIONS	STANDARD	PRO PRO	ELITE
EXTERNALLY HEATED HOSE (EH) PACKAGES AVAILABLE	Yes	Yes	Yes
INTERNALLY HEATED HOSE (IH) PACKAGES AVAILABLE	Yes	Yes	Yes
WHIP HOSE LENGTH INCLUDED IN PACKAGES	10 ft Whip in EH packages, 20 ft Whip in IH packages	10 ft Whip in EH packages, 20 ft Whip in IH packages	20 ft Whip
ITEMS INCLUDED IN SINGLE HOSE PACKAGE	Reactor, Whip Hose, 1 -50 ft Hose	Reactor, Whip Hose, 1 -50 ft Hose	Reactor, Whip Hose, 1 -50 ft Hose, Eng. CAN Cable
ITEMS INCLUDED IN MULTI-HOSE PACKAGE	Reactor, Whip Hose, 2 -100 ft IH Hoses 4 - 50 ft EH Hoses	Reactor, Whip Hose, 2 -100 ft IH Hoses 4 - 50 ft EH Hoses	Reactor, Whip Hose, CAN Cable 2 -100 ft IH Hoses 4 - 50 ft EH Hoses

SPRAY FOAM FLOW CHART



POLYUREA FLOW CHART



8

ADM TOUCHSCREEN

NEW TOUCHSCREEN CONTROL

Easier to Control and Access Information

The new larger interface provides simple touchscreen operations and makes the Reactor easy to operate. All the necessary spray information and control is on one screen, making it intuitive and easy to understand. New setup menus offer more controls than ever for owners and managers to optimize the machine for their business needs.

REACTOR CONNECT

Remote Monitoring is Always Within Reach

Reactor Connect is designed for both Sprayers and Owners/Managers alike. Use Reactor Connect to track ratios receive alerts and view data directly from your smartphone. As a result, owners/managers can monitor rigs. access reports, troubleshoot issues from anywhere and get the crew back to work quickly.

Independent Hose Inlet Material Intelligence Temperaturess • Quickly see temperature, Hose temperatures will follow the pressure and volume of A and B material set points to help A and B material remaining optimize your spray pattern and maximize material yield ■ Home **KATALY**5T 08:16 B 0 \$ B 113% 113°F 122% 122°F 69°F 68°F 151 psi 151 psi 120°F 38.3gal 38.3gal ್ಲಿಂ -2°F +2°F 10437 A:B ISO RES cycles 1.00:1 00000 **1000** psi 212.6 1014 psi 1009 psi gal **Auto Pressure Balance System Modes**

• The Reactor will automatically

adjust temperatures to optimize

fluid pressures and maximize yield

* Picture shown represents an Elite model.

A and B Fluid **Temperature Set Points**

- Simplified operations with only two temperature set points
- With independently heated hoses, the A and B materials are heated to your exact A and B temperature setpoints

Ratio Assurance

 When equipped with flow meters, view real-time ratio performance

REACTOR CONTROL SCREEN - Reactor Connect App

- Adjust temperature and pressure points
- View drum levels
- Turn heat zones on/off
- View and reset cycle counter/material usage
- Turn system on/off
- Turn pump on/off
- Toggle between Spray, Park and Jog modes
- View ratio

MULTI-SYSTEM DASHBOARD - Reactor Connect App

- Current Reactor status
- Daily "power on" time
- Daily "spray" time
- · Daily material usage

ONLINE INTERFACE - Reactor Connect Website

- Create user accounts, company profiles and users
- Assign Reactors to your accounts
- Advanced Reactor analytics
- Control access
- GPS location maps
- Automated summary reports
- Customized reporting

Quickly change between Spray,

Jog and Park modes with the

touch of a button

GRACO EXPERTS BY YOUR SIDE

Experienced graco technicians can access your Reactor system and troubleshoot issues for you remotely

ADD YOUR DISTRIBUTOR FOR FURTHER HELP

Reactor Connect

102°F

115°

Reactor Analytics is a great tool for analyzing machine performance and quickly diagnosing possible issues. Add your Graco equipment distributor to your Reactor Connect company so they can offer assistance.



10

KATALYST CONTROL FOR REACTOR 3

Helps Eliminate the Largest Causes of Off-Ratio Issues

Katalyst, the new Reactor 3 software, provides the highest level system intelligence to optimize spray, eliminate ratio issues, improve yield, to help deliver quality results every time.



HOW TO **ACTIVATE KATALYST: Set-up is Simple**

- Install Core E1 transfer pumps on your new Reactor 3 Elite proportioner
- Turn on the machine and acknowledge "Electric Transfer Pumps" when prompted. That's it...your Katalyst software is enabled

IMPROVE YOUR MATERIAL YIELD USING KATALYST

Even a 5% yield improvement can mean big savings for your business. Calculate your own savings using the calculator below:

ANNUAL SAVINGS:	\$37,500
EST. YIELD IMPROVEMENT	5%
SETS PER YEAR	250
MATERIAL COST PER SET	\$3,000

* Individual yield improvement may vary.



KATALYST PROVIDES FULL **COMMUNICATION AND CONTROL**

professional results.

• Communication with the Core E1 pumps nearly eliminates two of the largest causes of off-ratio spraying

> - Air in the fluid stream: With Katalyst the system will automatically shut you down when run out of material so air does not enter into the fluid stream

- Improperly feeding the Reactor with material: Katalyst automatically adjusts power to the pumps to always provide optimal material feed to the Reactor. e.g., helping to eliminate feed issues with cold materials

• Communication with Xcelerator heated hoses allows for independent A and B hose heat adjustments and the option of automatic pressure balancing for improved yield



* Standard and Pro models can upgrade hardware to activate Katalyst System Intelligence.

CORE E1 TRANSFER PUMPS XCELERATOR HEATED HOSES

CORE E1 ELECTRIC TRANSFER PUMPS

Powerful, Quiet, Smart

Get in the flow with Graco's revolutionary NEW Core electric transfer pumps; designed to optimize material supply and minimize downtime. Quieter and less expensive to operate than traditional pneumatic pumps, the new electric pumps can communicate with the Reactor 3 to give you a fully-connected system.

C.RE

NEW SUPPLY PUMP SHUTDOWN

Senses when a drum is empty and automatically shuts down the transfer pumps and Reactor 3 proportioner before damage occurs, including air entering the system and that can compromise ratio.

NEW SMART SUPPLY

The software automatically monitors and adjusts Reactor 3 proportioner inlet pressures to optimize material feed and on-ratio performance. Maintains inlet pressure between 80 − 200 psi — boosting power to the transfer pump's electric motors when needed. Achieve Smart Supply when using Core E1 pumps with a Reactor 3 Elite model.



PATENT PENDING

With our exclusive ProConnect technology, you can guickly disconnect the motor from the pump lower and easily transfer the pump from drum to drum... even in low ceiling height rigs. Paying for taller rigs or having to tip the drum to remove the pump is no longer necessary.

TIP: Have an extra pump lower installed on your rig to make changing drums even faster and cleaner.

CONNECTIONS MADE EASY!

Connecting your motor to the lower just got as easy as 1, 2, 3.



1 Loosen T-handle



2. Open Pump Clamp



3. Slide Electric Motor





That's equivalent to reducing the sound in your rig from being as loud as a motorcycle to that of a car.

NEW XCELERATOR HEATED HOSES

Faster to Heat, Lighter Weight, Improved Flexibility

Graco's new Xcelerator heated hoses provide more options and control than ever. All Xcelerator hoses are designed to provide full independent A and B temperature control. This provides more precise pressure balancing and improved material yield. New robust construction provides longer life and reduced maintenance.

PATENT PENDING

HOSE CONNECTIONS THAT ARE LIGHTWEIGHT AND ROBUST

Graco's new electrical connectors are designed with the user in mind

Pin and Socket Connectors

- Male/Female connectors provide a strong, reliable electric connection
- **Gasket and O-Ring Seal**
 - Provides moisture-proof electrical connection
- **Keyed Feature**
 - Unique keys on A and B connectors prevent incorrect connections



GRACO'S NEW INTERNAL HEATED HOSE HAS THE SMALLEST, LIGHTEST WEIGHT CONNECTIONS IN THE INDUSTRY

The robust, compact design allows the heating element to enter/exit the fluid stream at each hose joint without adding significant size or weight.

- 1 Heating Wire
 - Heating wire is located in hose ID for direct material contact and quick heating
- Wire Seal Nut/Ferrule/0-ring/Bushing
 - These components allow the heating wire to transition out of fluid and provide a proper seal
- 3 Crimp Connector
 - Connects the heating wire to the multi-strand wire



Xcelerator

DESIGNED FOR SPEED AND RELIABILITY

Fully-independent A and B temperature control

· Internally heated and externally heated options

• Internally heated hoses available in both

50 ft and 100 ft lengths: Minimizes fluid

• Optimized for Resistance Control Mode:

Reduces maintenance and issues

with no cables or sensors required

and electrical connections

Standard – Spray Foam Proportioners & Packages

REACTOR 3 E-20

26R310	Reactor 3, E-20, Standard, 7kW Heat
ESR310	Package: 50 ft ext heated hose, 10 ft whip
EHR310	Package: 50 ft ext heated hose (qty 4), 10 ft whip
ISR310	Package: 50 ft int heated hose, 20 ft whip
IHR310	Package: 100 ft int heated hose (qty 2), 20 ft whip

REACTOR 3 E-30

26R330	Reactor 3, E-30, Standard, 10kW Heat
ESR330	Package: 50 ft ext heated hose, 10 ft whip
EHR330	Package: 50 ft ext heated hose (qty 4), 10 ft whip
ISR330	Package: 50 ft int heated hose, 20 ft whip
IHR330	Package: 100 ft int heated hose (qty 2), 20 ft whip

Standard – Polyurea Proportioners & Packages



REACTOR 3 E-XP1 26R320 Reactor 3, E-XP1, Standard, 10kW Heat

EHR320	Package: 50 ft ext heated hose (qty 4), 10 ft whip
ISR320	Package: 50 ft int heated hose, 20 ft whip
IHR320	Package: 100 ft int heated hose (qty 2), 20 ft whip

ESR320 Package: 50 ft ext heated hose, 10 ft whip

REACTOR 3 E-XP2

26R340	Reactor 3, E-XP2, Standard, 15kW Heat
ESR340	Package: 50 ft ext heated hose, 10 ft whip
EHR340	Package: 50 ft ext heated hose (qty 4), 10 ft whip
ISR340	Package: 50 ft int heated hose, 20 ft whip
IHR340	Package: 100 ft int heated hose (qty 2), 20 ft whip

Pro – Spray Foam Proportioners & Packages

REACTOR 3 E-20

26R311	Reactor 3, E-20, Pro, 7kW Heat
ESR311	Package: 50 ft ext heated hose, 10 ft whip
EHR311	Package: 50 ft ext heated hose (qty 4), 10 ft whip
ISR311	Package: 50 ft int heated hose, 20 ft whip
IHR311	Package: 100 ft int heated hose (qty 2), 20 ft whip
26R313	Reactor 3, E-20, Pro, 10kW Heat
26R313 ESR313	Reactor 3, E-20, Pro, 10kW Heat Package: 50 ft ext heated hose, 10 ft whip
	· · ·
ESR313	Package: 50 ft ext heated hose, 10 ft whip

REACTOR 3 E-30

26R331	Reactor 3, E-30, Pro, 10kW Heat
ESR331	Package: 50 ft ext heated hose, 10 ft whip
EHR331	Package: 50 ft ext heated hose (qty 4), 10 ft whip
ISR331	Package: 50 ft int heated hose, 20 ft whip
IHR331	Package: 100 ft int heated hose (qty 2), 20 ft whip
26R333	Reactor 3, E-30, Pro, 15kW Heat
ESR333	Package: 50 ft ext heated hose, 10 ft whip
EHR333	Package: 50 ft ext heated hose (qty 4), 10 ft whip

ISR333 Package: 50 ft int heated hose, 20 ft whip

IHR333 Package: 100 ft int heated hose (qty 2), 20 ft whip

CSR332 Package: Reactor E-30 Elite, 50 ft int heated hose,

20 ft whip, engine cable, Core E1 pump kit

20 ft whip, engine cable, Core E1 pump kit

CHR332 Package: Reactor E-30 Elite, 100 ft int heated hose (qty 2),

Pro – Polyurea Proportioners & Packages

REACTOR 3 E-XP1

26R321	Reactor 3, E-XP1, Pro, 10kW Heat
ESR321	Package: 50 ft ext heated hose, 10 ft whip
EHR321	Package: 50 ft ext heated hose (qty 4), 10 ft whip
ISR321	Package: 50 ft int heated hose, 20 ft whip
IHR321	Package: 100 ft int heated hose (gtv 2), 20 ft whip

REACTOR 3 E-XP2

26R341	Reactor 3, E-XP2, Pro, 15kW Heat
ESR341	Package: 50 ft ext heated hose, 10 ft whip
EHR341	Package: 50 ft ext heated hose (qty 4), 10 ft whip
ISR341	Package: 50 ft int heated hose, 20 ft whip
IHR3/11	Package: 100 ft int heated hose (atv. 2), 20 ft whin

Elite – Spray Foam Proportioners & Packages

Complete packages include Reactor Elite proportioner, Internally Heated Hoses and Core E1 Pumps



REACTOR 3 E-20	REACTOR 3 E-30	
26R312 Reactor 3, E-20, Elite, 10kW Heat	26R332 Reactor 3, E-30, Elite, 15kW Heat	

Package: 50 ft ext heated hose, 20 ft whip, engine cable	ESR332	Package: 50 ft ext heated hose, 20 ft whip, engine cable
Package: 50 ft ext heated hose (qty 4), 20 ft whip, engine cable	EHR332	Package: 50 ft ext heated hose (qty 4), 20 ft whip, engine cable
Package: 50 ft int heated hose, 20 ft whip, engine cable	ISR332	Package: 50 ft int heated hose, 20 ft whip, engine cable
Package: 100 ft int heated hose (qty 2), 20 ft whip, engine cable	IHR332	Package: 100 ft int heated hose (qty 2), 20 ft whip, engine cab
	Package: 50 ft ext heated hose (qty 4), 20 ft whip, engine cable Package: 50 ft int heated hose, 20 ft whip, engine cable	Package: 50 ft ext heated hose (qty 4), 20 ft whip, engine cable EHR332 Package: 50 ft int heated hose, 20 ft whip, engine cable ISR332



Elite – Polyurea Proportioners & Packages

REACTOR 3 E-XP1

20N322	neactor 3, E-APT, Elite, TOKW neat
ESR322	Package: 50 ft ext heated hose, 20 ft whip, engine cable
EHR322	Package: 50 ft ext heated hose (qty 4), 20 ft whip, engine cable
ISR322	Package: 50 ft int heated hose, 20 ft whip, engine cable
IHR322	Package: 100 ft int heated hose (qty 2), 20 ft whip, engine cable

REACTOR 3 E-XP2

ESR342	Package: 50 ft ext heated hose, 20 ft whip, engine cable
EHR342	Package: 50 ft ext heated hose (qty 4), 20 ft whip, engine cable
ISR342	Package: 50 ft int heated hose, 20 ft whip, engine cable
IHR342	Package: 100 ft int heated hose (gtv 2), 20 ft whip, engine cabl

26R342 Reactor 3, E-XP2, Elite, 15kW Heat

Complete Elite Packages:

OCDOOL Decetor O F VD4 File 40kW Heet

Complete packages include Reactor Elite proportioner, Internally Heated Hoses and Core E1 Pumps

REACTOR 3 E-XP1

CSR322	Package: Reactor E-XP1 Elite, 50 ft int heated hos
	20 ft whip, engine cable, Core E1 pump kit

CHR322 Package: Reactor E-XP1 Elite, 100 ft int heated hose (qty 2), 20 ft whip, engine cable, Core E1 pump kit

REACTOR 3 E-XP2

CSR342	Package: Reactor E-XP2 Elite, 50 ft int heated hose,
	20 ft whip, engine cable, Core E1 pump kit
0110040	Destruction Deserting VDO Files 400 (Clark test of bosons)

CHR342 Package: Reactor E-XP2 Elite, 100 ft int heated hose (qty 2),

20 ft whip, engine cable, Core E1 pump kit





Complete Elite Packages:

CSR312 Package: Reactor E-20 Elite, 50 ft int heated hose,

20 ft whip, engine cable, Core E1 pump kit

20 ft whip, engine cable, Core E1 pump kit

CHR312 Package: Reactor E-20 Elite, 100 ft int heated hose (gty 2),

REACTOR 3 E-20

DON'T FORGET TO CHOOSE YOUR GUN SEPARATELY WHEN ORDERING YOUR REACTOR

Fusion PC Gun – A Perfect Rebuild in Seconds

REACTOR 3 E-30

For more information on additional gun options, see P&A brochure



Visit graco.com/reactor3 or ask your local authorized Graco distributor



graco.com/reactor3

REACTOR 3 HOSES REACTOR 3 ACCESSORIES



HOSE - SPRAY FOAM





96B125 **Hose:** 3/8 in, External, LP, 50 ft, RTD, Blue Mesh, 2000 psi
25P434 **Hose:** 3/8 in, Internal, LP, 50 ft, Xtreme-Wrap,™ 2000 psi
25P435 **Hose:** 3/8 in, Internal, LP, 100 ft, Xtreme-Wrap, 2000 psi
25P437 **Hose:** 3/8 in, Internal, LP, 50 ft, RTD, Xtreme Wrap, 2000 psi
45P438 **Hose:** 3/8 in, Internal, LP, 100 ft, RTD, Xtreme Wrap, 2000 psi



HOSE - POLYUREA





96B111 **Hose:** 3/8 in, External, HP, 50 ft, Blue Mesh, 3500 psi 96B145 **Hose:** 3/8 in, External, HP, 50 ft, RTD, Blue Mesh, 3500 psi



25P534 **Hose:** 3/8 in, Internal, HP, 50 ft, Xtreme-Wrap, 3500 psi
25P535 **Hose:** 3/8 in, Internal, HP, 100 ft, Xtreme-Wrap, 3500 psi
25P537 **Hose:** 3/8 in, Internal, HP, 50 ft, RTD, Xtreme Wrap, 3500 psi
25P538 **Hose:** 3/8 in, Internal, HP, 100 ft, RTD, Xtreme Wrap, 3500 psi



18E175 **Dual FTS Kit** for Independedntly Heated Hoses

18E176 **Xcelerator** Xtreme Wrap 50 feet 18E177 **Xcelerator** Xtreme Wrap 100 feet



CORE E1 TRANSFER PUMPS

26D004 **E1** Transfer Pump

26D005 **E1 PKG:** two pumps, Transfer Pump Controller, CAN cable

26D006 **E1 PKG:** two pumps, Transfer Pump Controller, CAN cable, fluid hoses 26D277 **E1 PKG:** two pumps, Transfer Pump Controller, CAN cable, fluid and air hoses



T4 TRANSFER PUMPS

26D001 **T4 Pump**

26D002 **T4 PKG:** two pumps, fluid hoses 26D003 **T4 PKG:** two pumps, fluid and air hoses

273295 **T4/E1:** Pump Lower, Carbon Steel, (Bung adapter not included)

25B395 **Kit:** Bung Adapter, 2 in, EZ Removal



KITS TO UPGRADE STANDARD AND PRO MODELS

18E212	Kit: Reactor 3, Ratio Assurance
18E246	Kit: Strainer, Reactor 3, Pair, Pro
18E247	Kit: Strainer, Reactor 3, Pair, Elite
18E248	Kit: Sensors, Inlet, Temperature, Pressure
255148	Kit: Large Recirculation Valve Set



REACTOR CONNECT KITS

18E242	Reactor Connect Kit: USA and Mexico, CAT-M, GPS
18E245	Reactor Connect Kit: Canada, CAT-1, GPS
18E244	Reactor Connect Kit: Var. Countries, CAT-M, GPS
18E243	Reactor Connect Kit: Var. Countries, 3G, GSM, GPS

18E211 **Kit:** R3,Remote Mount Bracket

ACCESSORY KITS

18E154 **Kit:** Reactor 3, Air Manifold 20A677 **Kit:** Reactor 3, Engine CAN, Harness 20A676 **Kit:** Reactor 3, Light Tower

18D314PKG **ADM:** Touchscreen screen protectors, 10 pack

25T859 **Kit:** TSL, bottle, (1 qt) 24M174 **Kit:** Drum level dip sticks



ADD CORE E1 TRANSFER PUMPS TO ANY REACTOR 3

A Complete System Fully-Connected From Drum to Gun

For more information on transfer pump options, see P&A brochure

FOR PART NUMBERS AND MORE DETAILS ON REACTOR 3 ACCESSORIES:

Visit graco.com/reactor3acc or ask your local authorized Graco distributor









Every Graco purchase comes with A+ Customer Service.

Questions? Call (844) 241-9499

For more information visit graco.com/contractor

©2022 Graco Inc. 3J0315 Rev. C 04/22 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. For more information on Graco's Intellectual Property see www.graco.com/patents or www.graco.com/trademarks. Product warranties are limited and subject to terms and conditions. Graco reserves the right to make changes at any time without notice.