

MATERIAL SAFETY DATA SHEET

PINNACLE ECOTITE 2.0 Part A

Prepared 11-04-2014

SECTION I CHEMICAL PRODUCT AND COMPANY INFORMATION

CHEMICAL NAME:	Polymeric MDI	PRODUCT USE:	Component of a Foam Insulation System
SUPPLIED BY:	Pinnacle West Enterprises Inc. 31897 Mercantile Way Abbotsford, BC, V2T 4C3	EMERGENCY CONTACT:	CHEMTREC 1-800-424-9300

SECTION II COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient	%(w/W)	CAS #	Exposure Limit	LD50/LC50
Diphenylmethane diisocyanate (MDI)	1-5	026447-40-5	TWA 0.005PPM PEL 0.02PPM	Not available/ 172-187mg/m ³ 4 hr (Rat)
Polymethylene polyphenyl isocyanate	40-55	009016-87-9	Not available	> 2000mg/kg (oral,rat)/ 490 mg/m ³ 4 hr (Inh: rat)
4'4'-Diphenyl methane diisocyanate	30-45	101-68-8	TWA 0.005 PPM PEL 0.02 PPM	> 10000mg/kg (Oral,rat)/ 490 mg/m ³ 4 hr (rat)

Consult local authorities for acceptable exposure limits

SECTION III HAZARDS IDENTIFICATION

Routes of Entry: Eye contact, Skin contact, Ingestion, Inhalation.

Acute Effects:

Eye Contact: May cause slight irritation.

Skin Contact: Prolonged or repeated exposure may cause skin irritation.

Inhalation: Excessive exposure may cause irritation of the upper respiratory tract and lungs.

Ingestion: Toxicity is low for ingestion

Chronic Effects: Chronic exposure to MDI may cause respiratory sensitization in susceptible individuals.

SECTION IV FIRST AID MEASURES

SKIN CONTACT	Clean exposed area with soap and water. Remove contaminated clothing and seek medical attention if irritation develops.
EYE CONTACT	Immediately flush thoroughly with water for at least 20 minutes lifting eye lids occasionally. Get prompt medical attention.
INHALATION	Remove to fresh air; give artificial respiration if not breathing. Get medical attention.
INGESTION:	Do not induce vomiting. If conscious, give victim 2 glasses of water. Never give anything to an unconscious person. Get medical attention immediately.

SECTION V FIRE FIGHTING MEASURES

Means of Extinction: Use large amounts of water spray, foam, dry chemical, or CO₂. Water spray to cool fire-exposed containers.
Special Procedures: None
Flashpoint: 199°C
Flammable Limits LEL (%): Not available
Flammable Limits UEL (%): Not available
Auto Ignition Temperature: Not available.
Hazardous Combustion Products: May produce carbon dioxide, carbon monoxide, oxides of nitrogen, dense black smoke, hydrogen cyanide, Isocyanates, Isocyanic Acid.
Sensitivity to Mechanical Impact: Not available
Sensitivity to Static Discharge: Not available

SECTION VI ACCIDENTAL RELEASE MEASURES

Spill or leak Procedure:
Evacuate all non-essential personnel. Ventilate. Eliminate all sources of ignition. Dike area to prevent spreading. Stop leak if safe to do so. Wear full protective equipment, including respiratory equipment during clean up. Prevent runoff into drains, sewers, and other waterways.

SECTION VII HANDLING AND STORAGE

Handling & Storage:
Store in a cool dry place away from any source of ignition. Handle in a well-ventilated area with local exhaust. Wear all personal protective equipment. Storage temperature (Min/Max: 10/38°C).
Special Shipping information: None

SECTION VIII EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal Protective Equipment: A positive pressure, supplied air respirator is required. An air purifying respirator is generally not recommended based on the poor warning properties of the product. At least an air-purifying respirator equipped with an organic vapour cartridge and particulate pre-filters must be worn.

Engineering controls: Local exhaust ventilation is recommended.

SECTION IX PHYSICAL AND CHEMICAL PROPERTIES

Odour: Musty Odour

Appearance: Brown Liquid

Physical State: Liquid

Odour Threshold: 200 ppm

Specific Gravity: 1.24 @25°C

Freezing Point: < 0°C

Viscosity: 50-100 cps

Vapour Density: No Data

Evaporation Rate: 3.6

Solubility in Water: NIL

%Volatile by Volume: 55-75%

Boiling Point: 208°C

pH: N/A

Vapour Pressure: <0.0001mmHg @20°C

SECTION X STABILITY AND REACTIVITY

Chemical Stability: Product is stable under normal conditions.

Conditions to avoid (if unstable): High temperatures, open flames and sparks.

Incompatibility (Materials to avoid): Water, amines, strong bases, alcohols. Copper Alloys.

Hazardous decomposition Products: Carbon Monoxide, carbon dioxide, oxides of nitrogen, dense black smoke, hydrogen cyanide, isocyanates, isocyanic acid.

Hazardous Polymerization: Polymerization will not occur.

SECTION XI TOXICOLOGICAL INFORMATION

LD50: oral-rat >2000 mg/Kg

LC50: inhalation-rat 490 mg/m³

Carcinogenicity: Not listed by IARC, NTP or regulated as a carcinogen by OSHA.

Teratogenicity: None Known.

Reproductive Effects: Not available.

Mutagenicity: None Known.

SECTION XII ECOLOGICAL INFORMATION

Ecological data is based on polymeric MDI.

Biodegradability: 0% Exposure Rate: 28 days

Bioaccumulation: Rainbow trout. Exposure time: 112 days, <1 BCF. Does not bioaccumulate.

Fish Toxicity: LC0: > 1000 mg/l, 96 hr, Zebra Fish

Fish Toxicity: LC0: > 3000 mg/l, 96 hr, Killifish

Fish Toxicity: EC50: > 1000 mg/l, 24 hr, Daphnia magna

SECTION XIII DISPOSAL CONSIDERATIONS

Disposal Procedure:

Comply with Federal, provincial, and local regulations on reporting releases.

Consult your local or regional authorities.

SECTION XIV TRANSPORT INFORMATION

TDG (TRANSPORTATION OF DANGEROUS GOODS) CLASSIFICATION: Not Regulated.

SECTION XV REGULATORY INFORMATION

WHMIS CLASSIFICATION: D2A, D-2B

Domestic Substance List (DSL): Yes

SECTION XVI OTHER INFORMATION

References: Canadian Guide of the Law and Regulations of the Transportation of Dangerous Goods. Controlled products regulations. Manufacturer's Material Safety Data Sheet. This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Other special considerations: No additional remark.

DATE: January 17, 2011 REVISION 5

PREPARED BY:

Pinnacle West Enterprises Inc.

31897 Mercantile Way

Abbotsford, B.C. V2T 4C3

MATERIAL SAFETY DATA SHEET

PINNACLE ECOTITE 2.0 Part B

Prepared 11-04-2014

SECTION I CHEMICAL PRODUCT AND COMPANY INFORMATION

CHEMICAL NAME: Polymeric Resin **PRODUCT USE:** Component of a Foam Insulation System

SUPPLIED BY: Pinnacle West Enterprises Inc.
31897 Mercantile Way
Abbotsford, BC, V2T 4C3 **EMERGENCY CONTACT:** CHEMTREC
1-800-424-9300

SECTION II COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient	Approximate Concentration	CAS #	Exposure Limits	LD50/LC50
Hydrofluoro-carbon	7-13%	460-73-1	Not available	> 20 000ppm 4hr (rat)/ Not available
2-Butoxyethanol	1-5%	111-76-2	Not available	470 mg/kg (rat) / 450 ppm/4hr (rabbit)

Consult local authorities for acceptable exposure limits

SECTION III HAZARDS IDENTIFICATION

Routes of Entry: Eye contact, Skin contact, Ingestion, Inhalation.

Acute Effects:

Eye Contact: Causes eye irritation. May cause temporary fogging of the eyes.

Skin Contact: Causes skin irritation. Inhalation: May cause respiratory tract irritation.

Ingestion: May be harmful if swallowed.

Chronic Effects: Overexposure to vapour may cause central nervous system depression. Overexposure may cause irregular heartbeat.

Chronic exposure may cause blood disorders. Chronic ingestion may cause kidney and liver damage.

See toxicological information (section 11)

SECTION IV FIRST AID MEASURES

SKIN CONTACT	Clean exposed area with soap and water. Remove contaminated clothing and seek medical attention if irritation develops.
EYE CONTACT	Immediately flush thoroughly with water for at least 20 minutes lifting eye lids occasionally. Consult a physician if irritation continues.
INHALATION	Remove to fresh air; give artificial respiration if not breathing. Get medical attention.
INGESTION:	Do not induce vomiting. Get medical attention immediately.

SECTION V FIRE FIGHTING MEASURES

Means of Extinction: Carbon dioxide, dry chemical, foam. In case of larger fires, water spray should be used.

Special Fire Fighting Procedures: Firefighter should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes. Cool fire exposed containers with cold water spray.

Flashpoint: Not available.

Flammable Limits LEL (%): Not available

Flammable Limits UEL (%): Not available

Auto Ignition Temperature: Not available.

Hazardous Combustion Products: May produce carbon dioxide, carbon monoxide, oxides of nitrogen. Dense black smoke. Other potentially toxic fumes.

Sensitivity to Mechanical Impact: Not applicable

Sensitivity to Static Discharge: Not applicable.

SECTION VI ACCIDENTAL RELEASE MEASURES

Spill or leak Procedure:

Evacuate all non-essential personnel. Utilize recommended protective clothing. Avoid breathing vapours and skin contact. Dike area to prevent spreading. Cover spill with inert material and collect for proper disposal. Wash area with soapy water and rinse. Prevent runoff into drains, sewers, and other waterways.

SECTION VII HANDLING AND STORAGE

Handling & Storage:

Store in a cool dry place away from any source of ignition. Handle in a well-ventilated area with local exhaust. Wear all personal protective equipment. Storage temperature (Min/Max: 18/29°C).

Special Shipping information: None

SECTION VIII EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal Protective Equipment: Safety glasses, chemical resistant gloves, protective clothing.

Ventilation: Local exhaust ventilation is recommended to prevent overexposure.

SECTION IX PHYSICAL AND CHEMICAL PROPERTIES

Odour: Amine Odour

Appearance: Blue Liquid

Physical State: Liquid

Odour Threshold: Not Available

Specific Gravity: Not Available

Freezing Point: Not Available

Boiling Point: Not Available

Vapour Density: Not Available

Evaporation Rate: Not Available

Vapour Pressure: Not Available

Solubility in Water: Not Available

% Volatile by Volume: Not Available

Viscosity: Not Available

SECTION X STABILITY AND REACTIVITY

Chemical Stability: Product is stable under normal conditions.

Conditions to avoid (if unstable): High temperatures, open flames and sparks.

Incompatibility (Materials to avoid): Oxidizing agents, isocyanates.

Hazardous decomposition Products: Carbon Monoxide, carbon dioxide, oxides of nitrogen. Dense black smoke. Other potentially toxic fumes.

Hazardous Polymerization: Polymerization will not occur.

SECTION XI TOXICOLOGICAL INFORMATION

LD50: Not available

LC50: Not available

Carcinogenicity: The components of this product are not listed by IARC, NTP or regulated as a carcinogen by OSHA.

Teratogenicity: Not available.

Reproductive Effects: Not available.

Mutagenicity: Not available.

SECTION XII ECOLOGICAL INFORMATION

Fish toxicity: Not available
Biodegradability: Not available

SECTION XIII DISPOSAL CONSIDERATIONS

Disposal Procedure:
Comply with Federal, provincial, and local regulations on reporting releases.
Consult your local or regional authorities.

SECTION XIV TRANSPORT INFORMATION

TDG (TRANSPORTATION OF DANGEROUS GOODS) CLASSIFICATION: Not Regulated.

SECTION XV REGULATORY INFORMATION

WHMIS CLASSIFICATION: D2A, D2B
Domestic Substance List (DSL): No

SECTION XVI OTHER INFORMATION

References: Canadian Guide of the Law and Regulations of the Transportation of Dangerous Goods. Controlled products regulations. Manufacturer's Material Safety Data Sheet. This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Other special considerations: No additional remark.

DATE: January 17, 2011 REVISION 2

PREPARED BY:

Pinnacle West Enterprises Inc.
31897 Mercantile Way
Abbotsford, B.C. V2T 4C3