# **Material Safety Data Sheet B-1050 RESIN**



**1701**, 3rd Avenue Shawinigan (QC), G9T 2W6, CANADA

Tel: 819 729-0395 Info@genyk.com

## Section 1 – PRODUCT & MANUFACTURER IDENTIFICATION

**MANUFACTURER PRODUCT** 

**GENYK** Inc. Commercial name: B-1050 Resin 1701,3<sup>e</sup> Avenue Chemical name: Blend of polyols

Shawinigan, Qc Material uses: Component of a semi-rigid

**G9T 2W6** polyurethane foam system

Tel: 819-729-0395

Fax: 819-729-0383

**WHMIS CLASSIFICATION VALIDATION DATE** Class D, Division 2B

January 2016

# Section 2 - COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS	CAS#	%	WEEL (AIHA TWA- 8hr
Blend of polyols	N/A	40 - 85	N/A
Blend of tertiary amines	N/A	0.5 - 3.5	N/A
Tris-iso-chloropropyl phosphate	13674-84-5	5 - 15	Not listed

### Section 3 - PHYSICAL AND CHEMICAL PROPERTIES

**Physical state** : Liquid Color : yellowish

Odor : slightly amine odor

**Specific gravity** : 1.05 - 1.10

: < 22 psi at 130°F (<152 kPa at 54°C) Vapor pressure

**Boiling/condensation point** : N/A Solubility in water : Good

Flash point :> 200°F (93°C)

### Section 4 – FIRE-FIGHTING MEASURES

**Extinguishing media** : Carbon dioxide, dry chemical or appropriate foam, water

spray for large fires.

Fire-fighting procedures : Firefighters should be equipped with self-contained breathing

apparatus to protect against potentially toxic and irritating fumes. Use cold water spray to cool fire-exposed containers to

minimize risk of rupture.

#### **Section 5 - STABILITY AND REACTIVITY**

**Hazardous polymerisation** : Hazardous polymerisation does not occur.

Stability : Stable.

**Materials to avoid** : Oxidizing agents, Isocyanates.

Hazardous decomposition : By fire: Carbon dioxide, Carbon monoxide; other aliphatic

**products** fragments which have not been determined.

### Section 6 - POTENTIAL HEALTH EFFECTS

**Route(s) of entry** : Skin contact, eye contact, inhalation and ingestion.

Eye : Can cause eye irritation. Symptoms include stinging,

tearing, redness, and swelling of eyes.

**Skin** : Can cause moderate skin irritation. Symptoms may include

redness and other skin damage. Additional symptoms of skin contact may include: allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin

effects).

**Inhalation** : Breathing of vapor or mist is possible. Breathing small

amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be

harmful.

**Ingestion** : Symptoms may include severe stomach and intestinal

irritation (nausea, vomiting and diarrhea), abdominal pain, and vomiting. Swallowing this material may cause digestive

tract burns.

# Section 7 - FIRST AID MEASURES

First aid for eyes : Flush eyes gently with water for at least 15 minutes while

holding eyelids apart; seek immediate medical attention.

First aid for skin : Remove contaminated clothing. Flush exposed area with large

amounts of water. If skin is damaged, seek immediate medical

attention. Launder clothing before reuse.

First aid for Inhalation : If symptoms develop, immediately move individual away from

exposure and into fresh air. Get medical attention if irritation

develops.

First aid for ingestion : If conscious, give 250 ml of milk or water to drink, and induce

vomiting. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. Obtain immediate medical attention.

#### Section 8 – ACCIDENTAL RELEASE MEASURES AND DISPOSAL CONSIDERATIONS

Action to take for spills/leaks : Absorb with sawdust or other absorbent and shovel into

suitable containers. Use appropriate personal protective equipment during clean up. Evacuate and keep unnecessary

people out of spill area.

**Clean-up**: Wash down surfaces with soap and warm water.

Waste disposal : Waste must be disposed of in accordance with federal,

state, and local environmental control regulations. Incineration is the preferred method. Empty containers must be handled with care due to product residue. Empty containers must be handled with care due to product

residue.

# **Section 9 – HANDLING PRECAUTIONS**

**Eye protection** : Use safety glasses or chemical goggles.

**Skin protection**: Use protective clothing impervious to chemicals. Selection

of specific items such as gloves, boots or apron will depend

on operation.

**Ventilation** : Local exhaust should be used to maintain a fresh supply of

air.

# Section 10 - HANDLING AND STORAGE

**Handling and storage** : Store in tightly closed containers in a cool, dry place. Avoid

**procedures** breathing vapours and contact with eyes or skin.

Storage temperature : 15°C to 30°C (59°F - 86°F).

### Section 11 – TRANSPORTATION INFORMATION

**Technical shipping name**: Polyol blend, Resin B-1050

**T.M.D. Classification** : Not regulated

**OMI Classification** : Not regulated IATA/OACI Classification : Not regulated

**Emergency phone number** : (613) 996-6666 CANUTEC.

# **Section 12 – REGULATORY INFORMATION**

The substance(s) in this product is/are on the Canadian Domestic Substances List.

### Section 11 – OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification.

Prepared by : GENYK Inc.

Date : January 2016